



DRI-GARD AP 7000

Premium grade waterborne acrylic wall sealer

Formulated to withstand alkaline moisture of new masonry walls, seals new porous walls, and prepares painted surfaces for subsequent finishes.

DESCRIPTION

- Waterborne
- Environmentally friendly & low VOC
- Non-toxic
- No added lead or mercury
- 100% waterborne acrylic
- Good hiding
- Good alkaline resistance
- Easy application

APPLICATION AREAS

- Concrete
- Masonry walls
- New porous walls
- Etc.

PRODUCT DATA

Appearances / Colours	White liquid
Chemical Base	Water-based, pure acrylic emulsion
Drying Time	At tropical ambient temperature of 30 °C Touch dry: within 30 minutes Hard dry: 1 hour Recoating: 2 hours
Film Thickness	WFT: 79 – 105 microns / 3.1 – 4.2 mils DFT: 30 – 40 microns / 1.2 – 1.6mils
Theoretical Consumption	10.8 m ² per L at recommended film thickness
Application Method	Brush or roller. Spraying is not recommended.
Thinning/Clean Up	Water
Shelf Life	Up to 12 months when stored in original containers in dry, cool conditions below 28 °C

APPLICATION

Surface to be painted must be free of dirt/grease, powdery residues, peeling/defective paint, suspected salt and chemical contaminations. Repair all surface defects (e.g., unevenness, cracks) with a suitable stucco compound such as Stucco-Flex+ or Stucco-Repair 1000 and smoothen via sandpaper (Grit 150).

LIMITATIONS

- Ensure container is tightly closed & out of reach of children and away from food and drinks.
- The product should be stored in a cool location.
- Ensure the surrounding is sufficiently ventilated during application and drying of Dri-Gard AP 7000.
- Ensure proper personal protective equipment is worn when using the product, such as gloves and eye protection.
- Avoid contact with skin or eyes. Any skin or eye contamination should be washed off with plenty of water or seek medical attention.
- Keep away from excessive heat, sparks or flame.

HEALTH & SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of these products, are given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance to the manufacturer recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

