



STUCCO-REPAIR 1000

Repair stucco for wall cracks & surface touch-ups

Ready-to-use, water-based acrylic stucco, suitable for aesthetical repairs, such as hairline cracks, resurface blemishes, rough areas and small holes, at both internal and external areas. It is water resistant and has excellent resistance to hairline cracking, flaking and chalking. Application is quick and efficient and a trowel skim appearance is easily achievable. Due to its alkaline resistance, finishing paints can be directly painted on.

FEATURES/BENEFITS

- Eco-friendly with Low VOC / Non-toxic formulation
- Excellent resistance to hairline cracking, flaking and chalking.
- Water resistant
- Quick and easy application
- Alkaline resistant
- Increase aesthetical value

APPLICATION AREAS

- Plasters
- Skim coat hairline cracks
- Resurface blemishes
- Surficial cracks
- Rough areas
- Small holes in cement rendered surfaces
- Rough areas
- Small holes in cement rendered surfaces
- Interior & exterior walls
- Overhead applications

PRODUCT DATA

Appearances / Colours	White (Other colours available upon request)
Packaging	5kg tub
Storage	12 Months from date of production
Storage Condition	Dry conditions at Temperature between 5 - 35 °C

GENERAL INFORMATION

Origin	Water-based acrylics
Specific Gravity	1.67 kg/L
Finishing	Matte
Material Appearance	Viscous Paste
Touch Dry	60 minutes
Overcoat	24 hours

SUBSTRATE

STUCCO-REPAIR 1000 is suitable for concrete and cement rendered walls. The repair surface should be clean and free of oil, grease, dust, dirt, mould release agents, and any other contaminants that may interfere with the adhesion. STUCCO-REPAIR 1000 should only be used for minor surficial imperfection repairs/coatings. For skim coats, it is highly advisable to use STUCCO-FLEX+ instead.

APPLICATION

Press STUCCO-REPAIR 1000 into cracks and holes using a flexible putty knife, and then smoothen over. Any areas with blemishes or rough surfaces may be troweled over. Large holes and areas with high humidity require a longer drying time. Sides of cracks may be chipped away to form a channel before repairing with STUCCO-REPAIR 1000. STUCCO-REPAIR 1000 is supplied ready-to-use. Force the paste into the channel and overfill to allow volume compensation, and overcoat with another layer of STUCCO-REPAIR 1000 if necessary. A waiting time of 4-5 hours is required between applications. Once set, sand down the surface with sandpaper and paint over the desired hiding level. STUCCO-REPAIR 1000 is compatible with any emulsion latex paints

TOOLS

Clean tools immediately with water before material dries up. Dried material may need to be removed mechanically.

LIMITATIONS

- Not suitable to be used with plastic or metal surfaces.

- Tub should be sealed tightly when not in use to prevent the product from drying up.
- Tub should be under cover, away from direct heat and stored upright.
- Applying too thick of STUCCO-REPAIR 1000 may cause improper curing/drying and may result in caking. This should be avoided.

HEALTH & SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of these products, are given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance to the manufacturer recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.