



SUPER LATEX A88

Synthetic polymer emulsion for cement mortars

Polymer emulsion for the enhancement of cement mortars in terms of water resistance, flexibility and bonding abilities. It is also able to strengthen the matrix of cement mortar.

FEATURES/BENEFITS

- Eco-friendly with low VOC / non-toxic formulation
- Water resistant & enhances bonding/flexibility of mortars
- Enhanced durability of plasters / screed
- Increases bonding between tiles and mortar
- Reduces risk of plaster cracks

APPLICATION AREAS

- Bonding agent
- Tile fixing mortars
- Screeds
- Exterior / interior wall plasters
- Thin layer patching mortars
- Walkways
- Repair mortars
- Masonry mortars

PRODUCT DATA

Appearances / Colors	Milky white liquid
Packaging	4L & 18L pails
Storage	12 months from date of production
Storage Condition	Dry conditions at temperature between 5-35 °C, away from direct sunlight

TECHNICAL DATA

Origin	Polymer emulsion
Specific Gravity	1.00 +/- 0.01
Chloride Content	N/A

www.dritechemicals.com

APPLICATION METHOD

Concrete must be clean, sound and free of all loose and friable material, cement laitance, oil and grease, etc. Absorbent surfaces should be saturated thoroughly with clean water.

To improve cement mortar, add Super Latex A88 directly to the mixture. It is not recommended to dilute Super Latex A88.

Clean all tools and application equipment with water immediately after use. Hardened or cured material can only be mechanically removed.

LIMITATIONS

- Renderings and floor toppings should be allowed to cure appropriately. This can be achieved with the application of a curing compound or with other curing practices such as covering with polythene sheets or damp hessian.
- Avoid excessive air-entrainment through over mixing.

HEALTH & SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of these products, are given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance to the manufacturer recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

